

RTCU Product Matix 2017-9																																																										
Product Name	Microprocessor	Encapsulation Dimensions	Encapsulation Type	Ingress Protection	NX32L Execution Architecture (Linux)	NX32 Execution Architecture	Platform SDK for user programs/modules in C	On-board Ethernet	On-board Wi-Fi	On-board Bluetooth Classic and Bluetooth LE	UMTS/HSPA engine (3G)	Quad Band GSM engine (2G)	Rail GSM-R	Dual SIM-card support	Gemalto eSIM compatible	RF ISM Communication (868 MHz)	Optional Wireless: M-Bus, Zigbee and KNX	GNSS receiver with GPS/GLONASS/QZSS	Dual GSM antenna (internal/external)	Interactive Voice Response (IVR) / DTMF	Number of Digital Input	Number of Digital Output (Solid State)	Number of Digital Output (Relay)	Number of Analog Input	Analog Input Resolution	Number of Analog Output	Analog Output Resolution	IEC60950-31 input support (S0)	I/O Expandable with MODBUS modules	Headset connector	Digital Audio with Speaker/Line-out and Microphone	1-Wire support (Button, Temperature sensors etc.)	Number of user DIP-Switches	Advanced 3D G-Sensor/Accelerometer	Number of RS232 channels	Number of dedicated RS485 channels	Number of RS485 channels (shared with RS232)	Full CAN 2.0B Controller	USB Host port for expansion (GPS, LAN, Camera, RFID, etc)	Number of LED Indicators Total / User / System	Power Supply	Internal Battery back-up (nominal)	Advanced Power-management	Zero-power mode	SD-CARD with FAT32 file-system	Internal Flash-drive	RAM Memory	System Flash memory	Storage for automatic datalogger	Persistent Dataflash	High Performance Persistent Memory (FRAM / VFRAM) (No Write Endurance Limitations)	Garmin Fleet Management / Navigation Enabled	Navigation and Messaging Platform support	Expandable with Wi-Fi / Ethernet	LCD Touch screen with 240x160 pixels	Graphical LCD-Display with keyboard		
RTCU NX-400 <i>New!</i>	Cortex-A5 32 Bit 500 MHz	160 x 89 x 54	9M DIN (plastic)	IP20	•	-	•	•	•	•	-	-	-	-	-	-	•	-	-	•	8	8	-	4	12b	4	12b	•	•	-	•	•	3	-	2	2	-	•	•	8/4/4	8-36V DC	2 Ah	-	-	•	up-to 512 MB	128 MB	528 MB	1 MB	7.5 MB	20KB	-	-	-	•	-		
RTCU MX2 turbo	ARM7 32 Bit 48 MHz	91 x 31 x 131	Aluminum	IP30	•	-	-	-	-	•	-	-	•	•	•	-	-	•	-	•	5	4	-	2	12b	-	-	-	•	•	-	•	•	2	•	2	1	-	•	-	7/4/3	8-36V DC	2 Ah	•	-	•	8 MB	2 MB	4.5 MB	1 MB	7.5 MB	20KB	•	•	•	-	-	
RTCU MX2 turbo-2G	ARM7 32 Bit 48 MHz	91 x 31 x 131	Aluminum	IP30	•	-	-	-	-	-	•	-	•	•	•	-	-	•	-	•	5	4	-	2	12b	-	-	-	•	•	-	•	•	2	•	2	1	-	•	-	7/4/3	8-36V DC	2 Ah	•	-	•	8 MB	2 MB	4.5 MB	1 MB	7.5 MB	20KB	•	•	•	-	-	
RTCU MX2 <i>encore</i> <i>with all on-demand options.</i>	ARM7 32 Bit 48 MHz	91 x 31 x 131	Aluminum	IP30	•	-	-	-	-	-	•	-	•	•	•	-	-	•	-	•	5	4	-	2	12b	-	-	-	•	-	-	•	•	1	1	-	•	-	7/4/3	8-36V DC	2 Ah	•	-	-	4 MB	2 MB	4.5 MB	1 MB	3.5 MB	20KB	•	-	•	-	-			
RTCU CX1 <i>warp 3G</i> <i>with all on-demand options.</i>	ARM7 32 Bit 48 MHz	92x 30 x 58	Plastic	IP66	-	-	-	-	-	•	-	-	-	-	•	-	-	•	-	-	2	2	-	1	10b	-	-	-	-	-	-	•	-	-	•	1	-	-	-	•	-	5/2/3	8-36V DC	0.9 Ah	•	-	•	4 MB	1 MB	2.2 MB	1 MB	3.5 MB	8KB	•	-	-	-	-
RTCU CX1 <i>warp-c 3G</i> <i>with all on-demand options.</i>	ARM7 32 Bit 48 MHz	92x 30 x 58	Plastic	IP66	-	-	-	-	-	•	-	-	-	-	•	-	-	•	-	-	2	2	-	1	10b	-	-	-	-	-	-	•	-	-	•	-	-	•	-	5/2/3	8-36V DC	0.9 Ah	•	-	•	4 MB	1 MB	2.2 MB	1 MB	3.5 MB	8KB	-	-	-	-	-		
RTCU DX4i <i>pro-2G</i>	ARM7 32 Bit 48 MHz	157 x 58 x 86	M36 DIN (plastic)	IP20	-	-	-	-	-	-	•	-	-	-	•	-	-	-	-	•	8	8	-	4	12b	4	10b	•	•	-	-	•	•	3	-	2	1	1	•	-	7/4/3	8-36V DC	2 Ah	•	-	•	4 MB	1 MB	2.2 MB	1 MB	3.5 MB	8KB	-	-	•	-	•	
RTCU DX4i <i>pro-3G</i>	ARM7 32 Bit 48 MHz	157 x 58 x 86	M36 DIN (plastic)	IP20	-	-	-	-	-	•	-	-	-	-	•	-	-	-	-	•	8	8	-	4	12b	4	10b	•	•	-	-	•	•	3	-	2	1	1	•	-	7/4/3	8-36V DC	2 Ah	•	-	•	4 MB	1 MB	2.2 MB	1 MB	3.5 MB	8KB	-	-	•	-	•	
RTCU AX9 <i>turbo</i>	ARM7 32 Bit 48 MHz	130 x 180 x 50	Plastic	IP65	•	•	•	-	-	•	-	-	-	-	•	-	-	•	•	•	5	-	4	4	12b	4	10b	•	•	-	-	•	•	3	-	2	1	1	-	-	7/4/3	8-36V DC 100-260VAC	2 Ah	•	-	•	8 MB	2 MB	4.5 MB	1 MB	7.5 MB	20KB	•	-	-	-	-	
RTCU AX9 <i>encore</i> <i>with RS485 on-demand option.</i>	ARM7 32 Bit 48 MHz	130 x 180 x 50	Plastic	IP65	•	-	-	-	-	-	•	-	-	-	•	-	-	•	•	•	5	-	4	2	12b	-	-	•	•	-	-	•	•	3	-	1	-	1	-	-	7/4/3	8-36V DC 100-260VAC	1 Ah	•	-	•	4 MB	2 MB	4.5 MB	1 MB	3.5 MB	20KB	-	-	-	-	-	
RTCU SX1 <i>series</i>	ARM7 32 Bit 48 MHz	175 x 42/54 x 126	Plastic	IP65	-	-	-	-	-	-	•	•	-	-	•	-	-	•	-	•	2	2	-	2	10b	-	-	-	-	-	-	•	•	3	•	1	-	-	-	•	-	5/2/3	8-36V DC	Up to 58 Ah	•	•	•	0.5 MB	1 MB	2.2 MB	0.5 MB	0.5 MB	8KB	•	-	-	-	-