

OxyGuard Gas Measurement Cell

Flow-Through Cell for Measuring Oxygen in Gas



Version without flow meter
Type number E021



Version with flow meter
Type number E023



Probe holder alone
Type number E022

The Gas Measurement Cell can be used to measure the purity of oxygen from oxygen generators, to monitor the oxygen content of gases containing oxygen and to monitor gases that must not contain oxygen. There are three types - 1) an enclosure with probe holder, 2) an enclosure with probe holder and flow meter and 3) a probe holder alone. The type of oxygen probe and transmitter are chosen to suit the actual application. The cell can be used with any OxyGuard transmitter or monitoring system, and can also be fitted with the Model 420 2-wire combined probe/transmitter.

The probe (and transmitter) must be ordered separately.

Enclosure size: h x b x d: 200 x 120 x 95 mm.
Material: ABS cabinet.
Connections: 1/4" hose, pipe thread or fitting as ordered.
Range: 0.0 to 100.0% oxygen or as ordered.
Cable length: 7 m or as ordered
Temperature: 0 to +40°C.

E06 Gas Measurement Cell brochure gb 0411

Data subject to change without notice



OxyGuard International A/S
Blokken 59, DK-3460 Birkerød, Denmark
Tel. +45 45822094, Fax +45 45821994
E-mail: oxyguard@oxyguard.dk

Distribuido por: AN CONSULT ESPAÑA, S.L. - Tel.: +34 916 130 031 - Email: comercial@anconsult.com